

Milesight






LoRaWAN® Sensor
LoRaWAN® Gateway
Industrial 4G/5G Router



5G · AIoT



Milesight IoT Product Portfolio

Picture	Model	Descriptions
	UC511-915M	<p>LoRaWAN Solenoid Valve Controller</p> <p>2 × DC Latching Solenoid Interface Come with Solar Panel 5-24 VDC with 4900 mAh chargeable battery IP67 rated</p>
	UC511-DI-915M	<p>LoRaWAN Solenoid Valve Controller</p> <p>2 × DC Latching Solenoid Interface 2 × Pulse Input Interface Come with Solar Panel 5-24 VDC with 4900 mAh chargeable battery IP67 rated</p>
	ACC-SOPAN	<p>Solar Panel Power</p> <p>Rated Power: 5 W Max Power: 10.12 W Max Current: 0.28 A Operating Temp: -40 ~ 85°C Weight: 0.6 kg (Applicable to UC501 and UC511)</p>
	UC512-915M	<p>LoRaWAN Solenoid Valve Controller</p> <p>2 × DC Latching Solenoid Interface 19000 mAh non-chargeable battery IP67 rated</p>
	UC512-DI-915M	<p>LoRaWAN Solenoid Valve Controller</p> <p>2 × DC Latching Solenoid Interface 2 × Pulse Input Interface 19000 mAh non-chargeable battery IP67 rated</p>

Remark:

"-915M", "-868M", "-470M" in the model refers to different LoRaWAN Frequency in option for different countries/regions, (e.g.)
 "-915M": KR920/AS923/AU915/US915
 "-868M": RU864/IN865/EU868
 "-470M": CN470

Tel: +86-592-5085280

Email: iot.sales@milesight.com

Web: www.milesight-iot.com